



MODEL

AirRite TT Series 118 HHL Indoor/Outdoor

STANDARD FEATURES

LUBRICATED BEARINGS W/ ZIRK FITTINGS BELT GUARD (PER OSHA STANDARDS)
AIR PROVING SWITCH ADJUSTABLE BURNER PROFILE DAMPERS MIDCO BURNER MAXITROL TEMPERATURE CONTROL SYSTEM HEAT & RUST RESISTANT INTERIOR FINISH INDUSTRIAL ENAMEL EXTERIOR FINISH AIR INLET SCREEN (OUTDOOR UNITS ONLY) UNIT MTD CONTROL MODULE 16 GAUGE CRS CASING (1) 18" DWDI FORWARD CURVED BLOWER FACTORY TESTED ELECTRONIC FLAME SUPERVISION TESTED TO ANSI Z83.4 & Z83.18

IF CURB IS REQUIRED: $2^{\circ} \times 2^{\circ}$ CURB ANGLE WILL BE ADDED TO BASE OF UNIT

PRELIMINARY

WEATHER-RITE

NOTE:
1.) DRAWING IS NOT TO SCALE.
2.) THIS SUBMITTAL ONLY APPLICABLE TO DIRECT FIRED BURNER.
3.) DUE TO SHIPPING REQUIREMENTS, SOME ELECTRICAL RECONNECTION MAY BE REQUIRED.