



MOTORIZED DISCHARGE DAMPER

BLOWER/BURNER HEAT SECTION V-BANK FILTER SECTION

FRESH AIR HOOD

MODEL

AirRite TT Series 218 HHL Outdoor

STANDARD FEATURES

ADJUSTABLE BURNER PROFILE DAMPERS MIDCO BURNER MAXITROL TEMPERATURE CONTROL SYSTEM HEAT & RUST RESISTANT INTERIOR FINISH INDUSTRIAL ENAMEL EXTERIOR FINISH AIR INLET SCREEN (OUTDOOR UNITS ONLY) AIR PROVING SWITCH BELT GUARD (PER OSHA STANDARDS) LUBRICATED BEARINGS W/ ZIRK FITTINGS UNIT MTD CONTROL MODULE FACTORY TESTED ELECTRONIC FLAME SUPERVISION 16 GAUGE CRS CASING (2) 18" DWDI FORWARD CURVED BLOWER TESTED TO ANSI Z83.4 & Z83.18

PRELIMINARY

IF CURB IS REQUIRED: $2^{\circ} \times 2^{\circ}$ CURB ANGLE WILL BE ADDED TO BASE OF UNIT

8.000 -

62.000

-- 24.000 -

72.000

NOTE:
1.) DRAWING IS NOT TO SCALE.
2.) THIS SUBMITTAL ONLY APPLICABLE TO DIRECT FIRED BURNER.
3.) DUE TO SHIPPING REQUIREMENTS, SOME ELECTRICAL RECONNECTION MAY BE REQUIRED.

WEATHER—RITE
HEATING AND VENTILATION, INC.