## MIN AR \ SUPPLY A∰ 36.000 26.000 8.000 20.000 38.000 RECIRC. DAMPER 24.750 11.250 42.000 16.188 20.000 HINGED ACCESS DOOR MOUNTING STAND APPROXIMATE GAS CONNECTION LOCATION INLET DAMPER BLOWER/BURNER HEAT SECTION V-BANK FILTER SECTION MOTOR COVER 15.500 22.750 **—** 33.000 **—** \|, 80.000 /|' 23.500 100.000 22.750 15.500 10.00 APPROXIMATE ELECTRICAL CONNECTION LOCATION SHIPMENT INSPECTION PORT & ACCES PANEL ACCESS PANEL BEARING COVER

## MODEL

AirRite TT Series 221 VTL Outdoor

## STANDARD FEATURES

ADJUSTABLE BURNER PROFILE DAMPERS MIDCO BURNER BELT GUARD (PER OSHA STANDARDS)
AIR PROVING SWITCH MAXITROL TEMPERATURE CONTROL SYSTEM HEAT & RUST RESISTANT INTERIOR FINISH INDUSTRIAL ENAMEL EXTERIOR FINISH AIR INLET SCREEN (OUTDOOR UNITS ONLY) LUBRICATED BEARINGS W/ ZIRK FITTINGS UNIT MTD CONTROL MODULE 16 GAUGE CRS CASING (2) 20" DWDI FORWARD CURVED BLOWER FACTORY TESTED ELECTRONIC FLAME SUPERVISION TESTED TO ANSI Z83.4 & Z83.18

PRELIMINARY

WEATHER—RITE
HEATING AND VENTILATION, INC.

NOTE:

1.) DRAWING IS NOT TO SCALE.

2.) THIS SUBMITTAL ONLY APPLICABLE TO DIRECT FIRED BURNER.

3.) DUE TO SHIPPING REQUIREMENTS, SOME ELECTRICAL RECONNECTION MAY BE REQUIRED.