



BLOWER/BURNER
 HEAT SECTION
 V-BANK
 FILTER
 SECTION
 INLET
 DAMPER
 FRESH AIR HOOD
 (SHIPPED BROKEN DOWN
 FIELD ASSEMBLY REQ)

MODEL
 AirRite TT Series 224 HHL Outdoor
STANDARD FEATURES

TESTED TO ANSI Z83.4 & Z83.18
 MAXITROL TEMPERATURE CONTROL SYSTEM
 ELECTRONIC FLAME SUPERVISION
 FACTORY TESTED
 16 GAUGE CRS CASING
 (2) 24" DWI FORWARD CURVED BLOWER
 UNIT MTD CONTROL MODULE
 LUBRICATED BEARINGS W/ ZIRK FITTINGS
 BELT GUARD (PER OSHA STANDARDS)
 AIR PROVING SWITCH
 AIR INLET SCREEN (OUTDOOR UNITS ONLY)
 INDUSTRIAL ENAMEL EXTERIOR FINISH
 HEAT & RUST RESISTANT INTERIOR FINISH
 ADJUSTABLE BURNER PROFILE DAMPERS
 MIDCO BURNER

IF CURB IS REQUIRED:
 2" x 2" CURB ANGLE WILL BE ADDED TO 3" BASE CHANNEL OF UNIT

"A"	"B"	GAS TRAIN SIZE
16,188	33,000	1", 1-1/4", 1-1/2"
16,188	35,000	2"
36,310	42,000	2-1/2", 3"

PRELIMINARY

NOTE:
 1.) DRAWING IS NOT TO SCALE.
 2.) THIS SUBMITTAL ONLY APPLICABLE TO DIRECT FIRED BURNER.
 3.) DUE TO SHIPPING REQUIREMENTS, SOME ELECTRICAL RECONNECTION MAY BE REQUIRED.

WEATHER-RITE
 HEATING AND VENTILATION, INC.