



MODEL
AirRite TT Series 230 HBL Outdoor

STANDARD FEATURES

TESTED TO ANSI Z83.4 & Z83.18
MAXITROL TEMPERATURE CONTROL SYSTEM
ELECTRONIC FLAME SUPERVISION
FACTORY TESTED
16 GAUGE CRS CASING
(2) 30" DWI FORWARD CURVED BLOWER
UNIT MTD CONTROL MODULE
LUBRICATED BEARINGS W/ ZIRK FITTINGS
BELT GUARD (PER OSHA STANDARDS)
AIR PROVING SWITCH
AIR INLET SCREEN (OUTDOOR UNITS ONLY)
INDUSTRIAL ENAMEL EXTERIOR FINISH
HEAT & RUST RESISTANT INTERIOR FINISH
ADJUSTABLE BURNER PROFILE DAMPERS
MIDCO BURNER

IF CURB IS REQUIRED:
2" x 2" CURB ANGLE WILL BE ADDED TO 3" BASE CHANNEL OF UNIT

"A"	"B"	GAS TRAIN SIZE
16,188	33,000	1", 1-1/4", 1-1/2"
16,188	33,000	2"
36,310	42,000	2-1/2", 3"

PRELIMINARY

- NOTE:**
- 1.) DRAWING IS NOT TO SCALE.
 - 2.) THIS SUBMITTAL ONLY APPLICABLE TO DIRECT FIRED BURNER.
 - 3.) DUE TO SHIPPING REQUIREMENTS, SOME ELECTRICAL RECONNECTION MAY BE REQUIRED.

WEATHER-RITE
HEATING AND VENTILATION, INC.