

575 VOLTS, 3 PHASE, 60 HERTZ

HP	0.5	0.75	1	1.5	2	3	5	7.5	10	15	20
*FLA	0.90	1.30	1.70	2.40	2.70	3.90	6.10	9.00	11.00	17.00	22.00
MCA	2.40	2.90	3.40	4.30	4.60	6.10	8.90	12.50	15.00	22.50	28.80
MOCP	3.00	3.90	4.80	6.40	7.10	9.80	14.70	21.30	25.80	39.30	50.50

HP	25	30	40	50	60	75	100	125
*FLA	27.00	32.00	41.00	52.00	62.00	77.00	99.00	125.00
MCA	35.00	41.30	52.50	66.30	78.80	97.50	125.00	157.50
MOCP	61.80	73.00	93.30	118.00	140.50	174.30	223.80	282.30

* FULL LOAD AMPS TAKEN FROM THE NATIONAL ELECTRICAL CODE, ARTICLE 430, TABLE 430.247-250. CONSULT THE NATIONAL ELECTRIC CODE (NFPA 70) FOR CONDUIT AND WIRE SIZING

 1100 7 Mile Road, Comstock Park MI 49321-0700	DRAWING DESCRIPTION	SCALE	TOLERANCES (UNLESS OTHERWISE NOTED)	
	MATL: NA	WEIGHT (lbs):	FRACTION	MACH WELD FAB
ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED	DO NOT SCALE DRAWING	REMOVE BURRS & SHARP EDGES	DECIMAL	ANGLE
	This sheet is for general information purposes only. Information can change without notice and should therefore not be used for construction or installation. All products must be set-up, assembled, installed and used in accordance with all applicable instructions, the provided instruction manual as well as requirements of governmental authorities. The information on this sheet is proprietary.		BLANK SIZE (in):	DRAWN BY:
		REV	CREATION DATE:	
		DWG. NO.	SHEET	
			1 OF 1	